

Specification

Model		SR-1(H)	SR-2(H)	SR-3(H)	SR-434(H)	SR-4(H)	SR-5(H)	SR-561(H)	SR-6(H)	SR-7(H)	SR-8(H)	
		SRA-1	SRA-2	SRA-3	SRA-434	SRA-4	SRA-5	SRA-561	SRA-6	SRA-7	SRA-8	
Capacity kW	*R22	50Hz	135	166	204	235	348	415	439	524	643	797
		60Hz	162	199	244	282	417	498	527	629	771	957
	*R134a	50Hz	89	110	131	162	236	277	292	355	404	542
		60Hz	106	132	157	195	284	333	350	426	485	650
	**R407C	50Hz	110	139	158	200	294	335	352	430	499	645
		60Hz	132	167	190	240	353	402	422	516	599	774
Displacement	m ³ /hr	50Hz	145.2	182.9	220.0	291.2	361.6	432.6	494.7	556.7	701.6	831.6
		60Hz	174.3	219.5	264.0	349.4	433.9	519.1	593.6	668.0	841.9	997.9
Male motor speed	RPM	3550/2950(60/50Hz)										
Capacity control	%	100/75/50/25(staring) or Linear capacity control (optional)										
Refrigerant		R-22/R-407C/R-134a										
Lubrication		Differential pressure feed lubrication										
Motor type		3 phases, 2 poles, induction motor										
Starting Method		Star-Delta starting										
Frequency	Hz	60/50										
Voltage	V	220,380,440,460 / 380~415										
Insulation		Class F										
Protection		Thermistor										
Oil heater	W	150					300					
Oil charge	Liter	9	11	11	13	13	13	13	19	23	23	
Weight for SR	kg	420	520	530	630	900	930	930	1,100	1,150	1,250	
Weight for SRA	kg	420	520	530	630	820	850	850	1,000	1,150	1250	
Noise Level(maximum)	dB	79	81	81	83	86	86	86	86	86	90	

Pursuing Excellence



Enriching Life