

### W-Series Specification

W-Series

Model	HP	Piston quantity	Piston displacement		Actual air delivery		Working pressure kg/cm <sup>2</sup> G	Cooling water required Liters/minute	Air tank	
			Liter/min.	CFM	Liter/min.	CFM			Volume Liter	Size mm.
			HCW-15	10	1L, 1H	807	28.50	565	20.00	20
HCW-16	15	1L, 1H	1,437	50.80	1,050	37.10	15	31		
HYW-15A	20	2L, 2H	1,614	57.00	1,130	40.00	20	56	660	Ø 780 X 1524
HYW-16A	30	2L, 2H	2,874	101.60	2,100	74.20	15	62		
HRW-16	50	4L, 2H	5,293	187.00	4,075	144.00	10	71		
HRW-16A	50	4L, 2H	4,879	172.40	3,415	120.60	18	75	1262	Ø 975 X 1850
HRW-18A	100	4L, 2H	12,420	438.90	9,190	324.70	10	120		
HRW-18B	100	4L, 2H	10,890	3846.00	7,780	274.80	18	126		
HRW-19	150	4L, 2H	20,270	716.30	16,419	580.20	7	193	150	Ø 390 X 1140
HCW-15S	10	1L, 1H	712	25.10	455	16.00	35	29		
HCW-16S	15	1L, 1H	1,178	41.50	718	25.30	35	42	300	Ø 485 X 1770
HYW-15S	20	1L, 2H	1,424	50.20	911	32.10	35	54		
HYW-16S	30	2L, 2H	2,357	83.20	1,437	50.70	35	64		
HRW-16S	50	3L, 3H	3,969	140.00	2,421	85.40	35	80	200	Ø 490 X 1300
SHYW-18	75	3 Stage, 3 Piston	5,051	178.00	3,840	135.50	60	97		

For other specification please contact us